



Vivotek **IP Surveillance System**

Network Camera **IP3112/3122/3132**

IP3112/3122/3132 are versatile network cameras powered by Vivotek optimal audio and video synchronizing technology. A built-in web server provides easy user interface for remote access to view and configure from anywhere in the world over the Internet with popular Microsoft Internet Explorer. Users just access streaming video/audio from the network camera like browsing any regular web site. More than high-performance network cameras, IP3112/3122/3132 also possess many advanced features to provide the ideal personal or SOHO solution for web attraction, remote surveillance, home security, video conference, etc....

Features

- Built-in camera and high-sensitivity microphone
- High performance and fully configurable MPEG4 compression
- Optimal synchronization of audio and video
- Built-in web server for global access
- Motion detection with three sensitive windows
- Weekly schedule for applications
- Pre/Post alarm snapshots
- Remote control for sensor and alarm
- Customizable homepage





• IP3112 NTSC CCD
• IP3122 PAL CCD



• IP3132 CMOS

Technical Specifications

IP3112/3122/3132



Model

- IP3112 NTSC CCD
- IP3122 PAL CCD
- IP3132 CMOS

System

- CPU: Trimedia PNX1300
- RAM: 8MB SDRAM
- ROM: 2MB FLASH ROM

Networking

- Protocol
TCP/IP, HTTP, SMTP, FTP, Telnet, NTP, DNS and DHCP
- Ethernet
10 baseT or 100 baseT Fast Ethernet auto negotiation

Video

- Algorithm supported
MPEG4(short header mode)
- Features
Adjustable image size, quality and bit-rate
Time stamp and text overlay
3 motion detection windows
- Resolution
IP3112(NTSC)
Up to 30 frames at 176x120
Up to 30 frames at 352x240
IP3122(PAL)
Up to 25 frames at 176x144
Up to 25 frames at 352x288
IP3132
Up to 30/25 frames at 160x120
Up to 30/25 frames at 320x240

Camera Specification

- IP3112/3122
1/4 inch color CCD image sensor
512(H)x492(V)(IP3112)/512(H)x582(V)(IP3122)
1 Lux / F2.0
AGC, AWB, AES
Electronic shutter: 1/60 (1/50)~1/100,000sec.
- IP3132
1/3 inch color CMOS sensor
640x480
2.5Lux / F1.4
AGC, AWB
Electronic shutter: 1/60~1/15,000sec.

Lens

- Standard CS-mount type, 6.0mm, F1.8

Audio

- 24kbps and 8kbps (optional)

Microphone

- Omni-directional
- Frequency
50 ~ 16000Hz
- S/N ratio
More than 60dB

General I/O

- 1 sensor input max. 12VDC 50mA
- 1 relay output max. 24VDC 1A / 125VAC 0.5A

LED Indicator

- Dual color system status indicator

Dimension

- Length: 138mm
- Width: 88.9mm
- Height: 57.2mm

Weight

- NET. 222g

Power

- Consumption:
IP3112/IP3122: near 5.4W
IP3132: near 4.4W
- Input: 100-240VAC, 50/60Hz, 0.4A
- Output: 12VDC, 1.5A

Operating Environment

- Temperature: 0~50°C(32~122°F)
- Humidity: 95% RH

EMI & Safety



- CE, FCC, BSMI

Viewing System Requirement

- Operation system: Microsoft Windows98 SE, ME, NT4.0, 2000, XP
- Browser: Internet Explorer5.0 or above

Free Bundled ST3201 Software

- Remote configuration and control for four devices
- Event-triggered, scheduled, manual recording
- Instant search with preview windows
- Fast/slow forward replay and pause
- Hard disk quota warning
- Scheduled backup
- AVI format export
- * 16-channel commercial version is available



All specifications are subject to change without notice.
All other trademarks are owned by their respective companies.